

# TECHNICAL SPECIFICATION

# FOF ROOF WINDOW



<b>Applicable</b>	<b>Cover parts</b>	<b>Pane</b>	
In public and domestic buildings	Aluminium, lacquered, RAL 7043	Construction	4-17-3
In heated, inhabited rooms	<b>Handle</b>	24 mm double glazing	✓
In roof pitch range of 15°- 90°	Ergonomically designed moulded zinc handle, lacquered	Low E	✓
Suitable on all roofings from 0 to 120 mm	<b>Hinge</b>	Gas ( argon )	✓
<b>Features</b>	Pivot hinge	Ug ( W/m2K )	1.1
Centre pivot		Total solar energy transmittance	0.62
Slim frame		Uw ( W/m2K )	1.5
Elegant bottom handle		Water tightness	E1200
Two passive ventilation positions via handle		Air permeability	Class 4
Easy installation		Resistance to wind load	Class C4
10 year guarantee		Sound reduction	30 (-1,-5) dB
<b>Material   Wood and finishing</b>		<b>Colour</b>	
Kiln-dried laminated pine wood		Natural wood	✓
Timber from PEFC certified forests			
Knot free visible surfaces			
Fungicide protection			
Acrylic lacquer			



MEASURES								
CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLEGLASS		
		Width	Height	Width	Height	Width	Height	Effective Light Area m <sup>2</sup>
FOF C2R	55 x 72 cm	55,0 cm	71,9 cm	39,8 cm	59,0 cm	37,3 cm	53,1 cm	0,198
FOF F6R	66 x 112 cm	66,0 cm	111,9 cm	50,8 cm	99,0 cm	48,3 cm	93,1 cm	0,449
FOF M4R	78 x 92 cm	78,0 cm	91,9 cm	62,8 cm	79,0 cm	60,3 cm	73,1 cm	0,440
FOF M6R	78 x 112 cm	78,0 cm	111,9 cm	62,8 cm	99,0 cm	60,3 cm	93,1 cm	0,561
FOF M8R	78 x 134 cm	78,0 cm	133,9 cm	62,8 cm	121,0 cm	60,3 cm	115,1 cm	0,694
FOF S6R	114 x 112 cm	114,0 cm	111,9 cm	98,8 cm	99,0 cm	96,3 cm	93,1 cm	0,896

COMPATIBILITY TABLE					
SIZE CODE	FLASHING Ø50 mm	BLACKOUT BLIND	ROLLER BLIND	VENETIAN BLIND	AWNINGBLIND
C2R	ZO C2R	DUR CXR	RHR C2A	PAR C2A	MIRCXA
F6R	ZO F6R	DUR F6R	RHR F6A	PAR F6A	MIRFXA
M4R	ZO M4R	DUR M4R	RHR M4A	PAR M4A	MIRMXA
M6R	ZO M6R	DUR M6R	RHR M6A	PAR M6A	MIRMXA
M8R	ZO M8R	DUR M8R	RHR M8A	PAR M8A	MIRMXA
S6R	ZO S6R	DUR S6R	RHR S6A	PAR S6A	MIRSXA

**10** | years  
guarantee

